



SKU : 162508

This series of table and column drilling machines is ideal for light drilling work in steel, cast iron and non-ferrous metals. They are used in workshops and industry for repairs and individual production.

- Universal use
- Compact and powerful
- Robust
- Low maintenance and quiet operation



TECHNICAL SPECS

WORKING AREA

Drilling capacity	32 mm
Column diameter	102 mm
Quill stroke	130 mm
Throat	230 mm
Spindle nose-to-table surface distance	750 mm
Spindle nose-to-foot distance	975 mm
Foot set up area (length x width)	300 mm
Table set up area	330 mm x 380 mm

HEADSTOCK

Spindle mount	3 MT
Spindle speed	160 1/min - 1880 1/min

DRIVE CAPACITY

Motor rating main drive	1.5 kW
-------------------------	--------

MEASURES AND WEIGHTS

Height	1760 mm
Weight	190 kg



PRODUCT DETAILS

- Coolant system
- Belt drive for low-noise operation, low-maintenance and robust design
- Precision spindle bearing - long life and high accuracy
- Table movement via hand-crank and gear rack
- Adjustable depth stop at the capstan handle
- Long quill stroke with precision guide
- Thick-walled column for maximum rigidity during machining of large parts



STANDARD EQUIPMENT

Drill chuck with key
 Tool-holder bits
 Drift bolt
 Coolant system
 Operating tools
 Operator instructions